Slimline 200/300/400L - Linkage Sprayer



MODEL SPECIFICATIONS						
РИМР	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP20/15: 20L/min. capacity 1500kPa pressure. BP60/20: 58L/min. capacity 2000kPa pressure.					
CONTROLS	BP20/15: 2 outlet control valve with pressure regulation. BP60/20: 3 outlet control valve with pressure regulation.					
TANK	Polytuff impact resistant polyethylene construction, moulded litre calibrations and non-spill screw-down lid with single breather.					
FRAME	Fully galvanised steel, cat. I & II linkage.					
AGITATION	Bypass agitation.					
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.					
FILTRATION	Lid strainer, suction line strainer.					
PTO DRIVESHAFT	Quality driveshaft with quick release pins and safety cover.					
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)		
K02S-20	920	740	920	60		
K03-20	1105	740	1070	70		
K04-60	1105	740	1310	75		

MODEL DESCRIPTION	CODE		
200L LINKAGE SPRAYER: BP20/15 pump, no boom			
300L LINKAGE SPRAYER: BP20/15 pump, no boom			
300L LINKAGE SPRAYER: BP60/20 pump, no boom			
400L LINKAGE SPRAYER: BP60/20 pump, no boom			
DEALER FITTED OPTIONS	CODE		
6m Field boom	032-044-6		
8m Field boom	032-044-8		
8 Jet vine boom (Used with BP60/20 pump only)	032-G		
10 Jet vine boom (Used with BP60/20 pump only)	032-H		
Undervine & mid row boom	032-HERB		
Boomless nozzle mounting kit (brass nozzle not included)	K99-11		
14L foam marker (single side)	K99-31		
16L foam marker (double side)	K99-39		
Economy hosereel, 30m hose (10mm ID), PA spray gun & extension lance	180E03010C		
Electric on/off control-3 section (GOYEN solenoids)			

Note: Not all options will fit all models. Extra charges may apply to factory fitment of some options.