## Trailed Economy Pasture Sprayer



Pictured: 1000L Economy Pasture sprayer with optional electric controls and undervine boom.

MODEL SPECIFICATIONS				
РИМР	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP60/20: 58L/min capacity 2000kPa pressure. BP125/20: 121L/min. capacity 2000kPa pressure			
CONTROLS	One lever 3 outlet control with pressure regulator mounted on adjustable arm.			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill screw-down lid with dual breathers.			
FRAME	Galvanised RHS steel construction, jockey wheel & height adjustable tow hitch.			
AGITATION	Bypass action.			

PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge mounted on adjustable arm.				
FILTRATION	Lid strainer and suction line strainer				
WHEELS	60mm straight single axle fitted with 15" tubeless tyres on galvanised rims (max speed rating 30km/h).				
РТО	Quality driveshaft with quick release pins & safety cover.				
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)	
J10-S60	1400	2600	1620	290	
J20-S105	1550	3500	2100	440	

MODEL DESCRIPTION	CODE
1000L PASTURE SPRAYER: BP60/20 diaphragm pump manual controls on pump.	
2000L PASTURE SPRAYER: BP125/20 diaphragm pump manual controls on pump.	
FACTORY OPTIONS	CODE
6m Field boom	032-044-6
6m Devil boom with hydraulic fold	032-19D
8m Field boom	032-044-8
8m Devil boom with hydraulic fold	032-25D
10m Field boom	032-014-10
10m Devil boom with hydraulic fold	032-32DM
6, 8 and 10m Devil boom hydraulic lift	032-19DL
Undervine and mid row boom	032-HERB
16L foam marker (double sided)	K99-39
Economy hosereel, 20m hose (10mm ID) and Triam spraygun	180E02012CT
Electric valve controls with pressure regulator and in cab pressure adjustment	K99-29
Bravo 180S automatic rate controller	
BP125/20, 121L/min capacity, 2000kPa driven by 5.5HP Honda	
Note: Not all options will fit all models. Extra charges may apply to fitment of some options.	