

Accessories



FREE STANDING SILMIX				
TANK	30L polyethylene tank with 455mm hinged lid.			
FUNCTION	Uses external water supply to activate venturi inductor at the base of the unit to transfer chemicals from hopper to sprayer tank. The same water supply operates the wash bar and drum rinse nozzle in the hopper. Transfer system requires minimum 2 Bar water pressure to operate (max 8 bar).			
CONTROLS	3 on/off taps to control: 1. Powder washer bar inside hopper. 2. Drum rinse nozzle. 3. Chemical transfer venturi. Also has ball valve at base of unit to isolate the tank from the induction venturi.			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
	640	640	830	15

MODEL DESCRIPTION	CODE
SILVAN 30L SILMIX ON FRAME	042J-06ST



Pictured: 57L Paddock foam marker

PADDOCK FOAM MARKER	
TANK	Polyethylene tank with moulded litre calibration indicators.
COMPRESSOR	Fully sealed, dust free compressor and electrics box with air breather.
CONTROLS	Double sided operation with electric cab control. Needle valve for foam output adjustment.
DROPPERS	2 foam droppers.
HOSE	16L: 16m of delivery hose. 57L: 36m of delivery hose.

MODEL DESCRIPTION	CODE
16L FOAM MARKER	042D-16S
57L PADDOCK FOAM MARKER	042D-57



Pictured: Reel tuff 12V remote reel



Pictured: Pitarm reel kit with 100m of 12mm nylon tube hose & Triarm 49 spray gun



Pictured: Economy reel kit with 30m of 10mm ag hose & PA spray gun

FACTORY OPTIONS	CODE
Reel tuff 12V remote reel (including bracket for super series linkage units)	K99-51
Economy reel, 20m x 12mm ag hose & Triarm 49 spray gun	180E02012CT
Economy reel, 30m x 10mm ag hose & PA spray gun with stainless steel extension	180E03010C
Pitarm reel, 100m x 12mm ag hose & Triarm 49 spray gun	180P10012C
Pitarm reel, 100m x 12mm nylon tube & Triarm 49 spray gun	180P10012T
Pitarm reel bracket (for sled units)	454-44

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.