

Trailed Compact Supaflo 1000L



Vineyards



Orchards



Pictured: 1000L Compact Supaflo

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with brass heads and manifold. IDS960:93L/min. capacity, 5000kPa pressure. IDS1401:135L/min. capacity, 5000kPa pressure.	HAND WASH TANK	15L fresh water hand wash tank.			
FAN SIZE	700mm axial flow type, 8 bladed fan with curved nylon reinforced blades and protective mesh cover.	FRAME	Galvanised steel with jockey wheel and adjustable drawbar.			
NOZZLES	Flip-over type for dilute/concentrate spraying. Ceramic HCC nozzles. 12 double sided nozzles (6 per side) twist on/off.	AGITATION	Pump bypass plus venturi agitator.			
GEARBOX	Single speed with neutral position, oil-bath type.	PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
CONTROLS	40 Bar electric section valves, master valve, electric pressure regulator and in-cab controls.	FILTRATION	Lid strainer and suction line filter.			
MAIN TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, flip-top easy open lid, 40mm drain valve.	WHEEL EQUIPMENT	50mm Duraflex axle. 2 x 15" tubeless tyres on painted rims (speed rating 30 km/h).			
FLUSH TANK	80L flush tank with top fill. Used to flush pump, filter, spray lines and nozzles.	PTO DRIVESHAFT	Quality driveshaft with quick release pins and safety cover.			
		HP REQUIRED	Minimum 40 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		AB11AF8R	2860	1100	1500	300
			Length measured with drawbar in shortest position.			

MODEL DESCRIPTION

SUPAFLO 1000L: IDS960 pump, 700mm fan & electric valve controls

CODE

AB11AF8R

FACTORY OPTIONS

IDS1401 pump, 135L/min. capacity, 5000kPa pressure

CODE

Two-sided deflector

D99-179

Two-sided conveyor

D99-92B

Bottom air deflectors

D99-177

Wide axle (1400mm)

D99-63

Bravo 180S automatic rate controller

D99-178

D99-143

Extra charges may apply to fitment of some options.