

Linkage P55DS Turbomiser



Vineyards



Orchards



Greenhouse



AVAILABLE WITH
TURBOMISER
HEAD OPTIONS
SEE PAGE 32



Pictured: P55DS 600L with optional Super Cannon head

MODEL SPECIFICATIONS

PUMP	CD32 centrifugal pump, 140L/min. constructed from toughened nylon. Stainless steel shaft & viton/ceramic seal.	TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill lids, hydro chemical mixer in larger basket, lids with basket strainers, separate in-built 18L fresh water hand wash tank.			
FAN SIZE	P55DS:550mm dia. turbine fan, 3700 rpm. Power consumed 50 kw/70HP.	FRAME	Galvanised RHS steel construction, cat II linkage.			
NOZZLES	Air shear.	AGITATION	Bypass and pneumatic.			
GEARBOX	Multiplication type through multi-grip, multi-vee belt and pulley, over-run free wheeling hub and oil bath fan housing.	FILTRATION	Lid strainer and suction line strainer.			
CONTROLS	Two sided electric on/off control with control box mounted in cabin. Rotary plate distribution regulators with 15 settings and manual pressure adjustment.	PTO DRIVESHAFT	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.			
PRESSURE GAUGE	Protected 100mm glycerine gauge fitted at front of sprayer.	HP REQUIRED	Minimum 70 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		GTM-P55DS (LESS HEAD)	1100	1450	1150	250

MODEL DESCRIPTION

600L P55DS LINKAGE TURBOMISER: P55DS fan (spray head not included)

CODE

GTM-P55DS

FACTORY OPTIONS

FACTORY OPTIONS	CODE
Vineyard head - 4 heads (4 x 5)	GT55D-40
Orchard Cannon head	GT55-13
Super Cannon head	GT55D-1
Hydraulic turntable for Super Cannon	GT55D-9
Bravo 180S automatic rate controller	GT-24

Note: Not all options will fit all models. Extra charges may apply to fitment of some options. Sprayer depicted with optional sprayhead.